



SILK

ILLUSIONS METALLICA



Drying Time



Surface dry: 1 hour
Hard dry: 6-8 hours

Dilution Ratio



200 ml water/1 litre of Metallica
for roller/brush application.
No dilution for design application

Coverage



Direct application: 130-150
sq. ft./ltr./coat*

*Coverage may vary due to factors
such as application methods, nature
of substrate, conditions etc.

Product Description

Silk Illusions Metallica is a premium water-based product. It is 100% acrylic emulsion paint for interior/exterior application. This special effect paint gives glossy metallic finish for various applications such as wall, wood, metal etc.

Recommended Use

To give metallic finish to:


- Previously painted surface
- Fresh/new surfaces
- Wooden/metal surfaces

How to apply



Step 1:

Apply 2 coats of Silk Luxury Emulsion (interior wall) & Weathercoat Smooth (exterior wall) as base coat. Let it dry for at least 6 - 8 hours before applying second coat. Allow it to dry for at least 6 - 8 hours.



Step 2:

Use tools specified in the recommended manner to create design with Silk Illusion Metallica.

Note: For large wall applications, complete the design in segments.

Please note:

- Stir well and strain before use
- Do not apply when ambient temperature is below 10°C
- Re-coat and drying of paint are tested at 30+/-2°C and 60-65% RH. Results may vary under different conditions
- Non-Flammable
- Tint with Berger Paints colourants only to get desired shade
- Store in a cool and dry place
- Keep out of reach of children and away from edibles
- In case of contact with eyes, wash immediately & seek medical advice
- For safety measures, refer to MSDS

Version No: BJN/05/2024. Please note that this data sheet supersedes all previous versions.

Berger Jenson & Nicholson (Nepal) Pvt. Ltd.

Berger House, 492, Tinkune, Koteshwor, Kathmandu /Phone: 01-5199218 (Hunting Line),

Toll Free No: 16600123434/ E-mail: customercare@bergernepal.com / Web: www.bergernepal.com / www.facebook.com/BergerPaintsNepal